


| | | | |
|--|---|--|----------------|
| A1. Model No.: | | A2. Product Name: | |
| SV-HDW135814CI | | 2.4GHz Digital Wireless 1080P HD Camera | |
| B1. Product Keywords: | |  | |
| 1) 1080P | | | |
| 2) Waterproof: IP69K | | | |
| 3) Nightvision distance: 1-3m | | | |
| 4) 10V-32V wide power supply input available | | | |
| 5) External power bank acceptable | | | |
| 6) Anti-vibration: ISO 16750-3 (Max. 17.3G) | | | |
| 7) Magnetic housing for easy installation | | | |
| B2. Key Specifications: | | | |
| Image Device | 1/2.9" CMOS | | |
| Effective Pixels | 1920 (H) x 1080 (V) | | |
| S/N Ratio | 38 | | |
| White Balance | Auto | | |
| BLC | Auto | | |
| Dynamic Range | 81dB | | |
| Operation Frequency | 2403MHz-2478MHz | | |
| Receiving Sensitivity | -78dBm | | |
| Video Codec | H.264 | | |
| Transmission Power | FCC: ≤26dBm CE: ≤20dBm MIC: ≤10dBm | | |
| Transmission Distance | FCC: ≤300m CE: ≤200m MIC: ≤60m | | |
| Modulation | FHSS | | |
| Delay | Wireless Monitor: 130ms Wireless Receiver: 170ms | | |
| Operating Temperature | -20°C ~ 70°C, RH95%MAX. | | |
| Storage Temperature | -30°C ~ 80°C, RH95%MAX. | | |
| Minimum Illumination | 0Lux | | |
| Night Vision Distance | 1-3m | | |
| Power Supply | DC10~32V | | |
| Power Consumption | 2W-2.6W | | |
| Waterproof IP Ratings | IP69K | | |
| Audio | No | | |
| Viewing Angle | 70° | | |
| C1. Accessories: | | | |
| 1- Manual | | 1- DC power cable | |
| 1- Phillips Flat Head Machine Screws | | | |
| D1. Packing: | | | |
| Weight Of Unit Product: | | Weight Of Export Carton: | |
| Dimension Of Giftbox: | 19.3*8.6*9.8cm | Dimension Of Export Carton: | 45*40.2*32.4cm |
| 20"/40"/40"HQ Qty: | | Qty Per Carton: | |
| E1. Payment Term: | | F1. Warranty Terms: | |
| | | 18 months of warranty | |
| G1. Certificates: | | H1. Price & Lead time: | |
| | | Sample | Lead time: |
| I1. Remarks: | | | |
| | | | |