



FEATURES

- Best picture quality (in combination with Digital LCD monitor)
- High resolution CCD camera (470,000 pixels)
- 1/3" Color CCD high resolution image sensor
- IP68 Waterproof Rating
- Diagonal 130° Viewing
- Adjustable Mirror/Normal Image
- Ultra low light performance
- Automatic Electronic Iris
- Built-in Microphone
- Built-in IR LED's
- Temp. -30°C ~ 80°C
- Vibration resistant
- Aluminum die-cast housing
- Anti-corrosive, chromate coating
- Waterproof screw type connector (IP67), 4-pin mini-DIN.

Specifications

| | |
|------------------------------|---|
| Image Sensor | 1/3" Color SONY SUPER HAD II CCD |
| Scanning System | PAL 470,000 pixels |
| Resolution | 520 TV Lines |
| S/N ratio | Better than 50dB (at AGC off) |
| Minimum Illumination | 0 lux (IR LED's on) |
| Power supply | DC 9 ~ 24V |
| Power Consumption | DC 9V, 170mA DC 24V, 60mA |
| Operating Temperature | -30°C to +80°C |
| Field of View angle | 130° (Diagonal), 110° (Horizontal), 81° (Vertical) |
| Dimension | 72(W) x 77(H) x 50(D) mm |
| Weight | 205g (total weight incl. bracket & sunvisor: 312g) |